

# Flexible Cables PVC Insulated

(Parallel Conductors Flat Cable)



1. Flexible Conductor
2. PVC Insulation

## Applications

- Highly flexible cable for very light uses in buildings.
- Suitable for low temperatures.

## Product Features

- **Type of Cable:** H03VH-H
- **Voltage:** 300/300V
- **Specifications:** ELOT EN 50525.02.31
- **Insulation:** PVC (ELOT EN 50363 - 3 - TYPE TI 1)
- **Max. Operating Temperatures (°C):** +70°C

Conductor Nominal Cross-Sectional Area	External Diameter (Max.)	Net Weight (Approx.)	Insulation Thickness
mm <sup>2</sup>	mm	Kg/Km	mm
2 x 0.75	3.2 x 6.4	30	0.8

The mentioned values are these which have been measured in our laboratory, under typical conditions. They can be modified without prior notice. You are kindly requested to assert their validity before any special use.

**ISOPIPE® S.A.**

[www.isopipe.eu](http://www.isopipe.eu)

**GREECE**  
**Head Office:**  
 Nafpliou & Daskalogianni  
 144 52 Metamorfofi Attikis  
 T.: +30 210 28 28 603  
 F.: +30 210 28 19 210  
 E.: export@isopipe.gr

**Plant:**  
 73rd km Nat. Road Athens - Lamia  
 341 00 Ritsona Halkida  
 T.: +30 22620 89 800  
 F.: +30 22620 72 006  
 E.: export@isopipe.gr

**SPAIN**  
**Barcelona:**  
 C/ Costa l Deu 71 - 79 (esq. C/ Tamarit)  
 08205, Sabadell, Barcelona, España

**Madrid:**  
 Calle Pedro Duque, 5,  
 Poligono Industrial GITESA,  
 28.814- Daganzo de Arriba (Madrid),  
 Madrid Community

T.: +34 93 879 1195  
 F.: +34 93 879 1313  
 E.: pedidos@isopipe.es

**UNITED KINGDOM**  
**Head Office:**  
 178 Seven Sisters Road  
 London N7 7PX  
 United Kingdom

**Warehouse:**  
 Airfield Industrial Estate Warboys,  
 Huntingdon  
 Cambridgeshire PE28 2SH  
 United Kingdom

T.: +30 210 28 28 603  
 E.: orders@isopipe.eu