

www.isopipe.eu

No. 1020 - CPD - 010030388

DECLARATION OF PERFORMANCE

Unique identification code of the

product-type:

ISOPIPE HP TC Tubes and Sheets

Intended use/es:

Manufacturer:

ThIBEII: Flexible Elastomeric Foam,

intended to be

used as Thermal insulation for building

equipment

and industrial installations.

Isopipe SA, 26 Nafpliou str.,144 52

Metamorfosi, Athens, Greece

Plant: 68° km Nat. Road Athens-Lamia,

34100 Ritsona, Halkida, Greece

System/s of AVCP:

3

Harmonised standard:

EN 14304:2009+A1:2013

Notified body:

NB 1020

Declared performance/s:

| Essential characteristics | Performance | |
|---------------------------|--------------------|--|
| Thermal Conductivity | -20°C - 0.031 W/mk | |
| | 0°C - 0.033 W/mk | |
| | 20°C - 0.035 W/mk | |
| | 30°C - 0.036 W/mk | |



Rebuild the future!

www.isopipe.eu

| Reaction To Fire | Tubes: EL Sheets: E |
|--|--|
| Durability of thermal resistance against ageing/degradation Durability of thermal resistance | Dimensional stability (1) Minimum service temperature ST(-) -50 (=-50°C) Maximum service temperature ST(+) 110 (=110 °C) |
| against high temperature Durability of reaction to fire against high temperature | (2) |
| Durability of reaction to fire against ageing / degradation | (2) |
| Compressive strength | (3) NPD |
| Water permeability Water vapour permeability / Water vapour diffusion resistance | 10.000 |
| Rate of release of corrosive substances | CI-<300ppm |
| Acoustic (absorption) index | NPD |
| Release of dangerous substances to the indoor environment | (4) |
| Continuous glowing combustion | (4) |

- 1) The thermal conductivity of FEF does not change with time.
- 2) The fire performance of FEF does not change with time.
- 3) Compressive strength is not applicable for FEF products.
- 4) European test methods are under development

NPD = No Performance Determined.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Ritsona, 08/01/25

Signed for and on behalf of the manufacturer by:

Markati Athanasia,

Quality Assurance Manager

