

www.isopipe.eu

DECLARATION OF PERFORMANCE

No. 1020 - CPD - 010030388

Unique identification code of the product-type:

ISOPIPE ISOSOL HT-HF

Intended use/es:

Manufacturer:

ThibEii: Flexible Elastomeric Foam,

intended to be

used as Thermal insulation for building

equipment

and industrial installations.

Isopipe SA, 26 Nafpliou str.,144 52

Metamorfosi, Athens, Greece

Plant: 68° km Nat. Road Athens-Lamia,

34100 Ritsona, Halkida, Greece

System/s of AVCP:

3

Harmonised standard:

EN 14304:2009+A1:2013

Notified body:

NB 1020

Declared performance/s:

Essential characteristics	Performance
Thermal Conductivity	0°C - 0.040 W/mk 40°C - 0.045 W/mk
Reaction To Fire	Tubes: EL
Durability of thermal resistance	Dimensional stability (1)



Rebuild the future!

www.isopipe.eu

against ageing/degradation	Minimum service temperature ST(-) -50 (=-50°C)
Durability of thermal resistance against high temperature	Maximum service temperature ST(+) 150 (=110 °C)
Durability of reaction to fire against high temperature	(2)
Durability of reaction to fire against ageing / degradation	(2)
Compressive strength	(3)
Water permeability	NPD
Water vapour permeability / Water vapour diffusion resistance	4000
Rate of release of corrosive substances	NPD
Acoustic (absorption) index	NPD
Release of dangerous substances to the indoor environment	(4)
Continuous glowing combustion	(4)

- 1) The thermal conductivity of FEF does not change with time.
- 2) The fire performance of FEF does not change with time.
- 3) Compressive strength is not applicable for FEF products.
- 4) European test methods are under development

NPD = No Performance Determined.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Ritsona, 08/01/25

Signed for and on behalf of the manufacturer by:

Markati Athanasia,

Quality Assurance Manager

