Technical Data Sheet

ISOTAPE®

Self-Adhesive Insulation Tape

SOLAR Polymer

PVC

UV PLUS Pet-Al-Pe

Properties	Self-Adhesive Insulation Tape	SOLAR Polymer	PVC	UV PLUS Pet-Al-Pe
Length	10m & 15m	10m & 25m	33m	10m & 25m
Width	50mm			
Support	PES/ PVA scrim			
Interliner	Yellow 90g/ m² double sided siliconized			Yellow 90g/ m² double sided siliconized
Adhesive Weight	60g/ m²	70g/ m²		
Adhesive Thickness	60μm	70μm		
Upper Temperature (°C)	+90°C		+100°C	
Lower Temperature (°C)	-40°C			
Adhesive Strength (based on AFERA 5001)	min 18 N/ 25mm	22 N/ 25mm	40 N/ 25mm	22 N/ 25mm
Colour	Black	Silver, Black & White	Black & White	Aluminum

The mentioned values are these which have been measured in our laboratory, under typical conditions.
They can be modified without prior notice. You are kindly requested to assert their validity before any special use.

ISOPIPE® S.A.

www.isopipe.eu

GREECE
Head Office:
Nafpliou & Daskalogianni
144 52 Metamorfosi Attikis
T.: +30 210 28 28 603
F.: +30 210 28 19 210
E.: export@isopipe.gr

Plant:
73rd km Nat. Road Athens - Lamia
341 00 Ritsona Halkida
T.: +30 22620 89 800
F.: +30 22620 72 006
E.: export@isopipe.gr

SPAIN
Barcelona:
C/ Costa i Deu 71 - 79 (esq. C/ Tamarit)
08205, Sabadell, Barcelona, España

Madrid:
Calle Pedro Duque, 5,
Polígono Industrial GITESA,
28.814- Daganzo de Arriba (Madrid),
Madrid Community

T.: +34 93 879 1195
F.: +34 93 879 1313
E.: pedidos@isopipe.es

UNITED KINGDOM
Head Office:
178 Seven Sisters Road
London N7 7PX
United Kingdom

Warehouse:
Airfield Industrial Estate Warboys, Huntingdon
Cambridgeshire PE28 2SH
United Kingdom

T: +44 (0) 208 299 9545
E: orders@isopipe.eu

© 06.2019